

Product data sheet

Characteristics

GV3ME80

Motor circuit breaker, TeSys GV3, 3P, 56-80 A, thermal magnetic, screw clamp terminals



⚠ Discontinued

Main

| | |
|----------------------|------------------|
| Range | TeSys |
| Product name | TeSys GV3 |
| Device short name | GV3ME |
| Device application | Motor |
| Trip unit technology | Thermal-magnetic |

Complementary

| | |
|---|---|
| Poles description | 3P |
| Network type | AC |
| Utilisation category | AC-3 conforming to IEC 60947-4-1 Category A conforming to IEC 60947-2 |
| Network frequency | 50/60 Hz conforming to IEC 60947-4-1 |
| Fixing mode | 35 mm symmetrical DIN rail: clipped Panel: screwed (with 2 x M4 screws) |
| Operating position | Any position |
| Motor power kW | 37 kW at 400/415 V AC 50/60 Hz 55 kW at 690 V AC 50/60 Hz 45 kW at 500 V AC 50/60 Hz |
| Breaking capacity | 100 kA Icu at 230/240 V AC 50/60 Hz conforming to IEC 60947-2 15 kA Icu at 400/415 V AC 50/60 Hz conforming to IEC 60947-2 4 kA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2 10 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 2 kA Icu at 690 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Ics] rated service short-circuit breaking capacity | 100 % at 690 V AC 50/60 Hz conforming to IEC 60947-2 100 % at 500 V AC 50/60 Hz conforming to IEC 60947-2 100 % at 230/240 V AC 50/60 Hz conforming to IEC 60947-2 50 % at 400/415 V AC 50/60 Hz conforming to IEC 60947-2 60 % at 440 V AC 50/60 Hz conforming to IEC 60947-2 |
| Control type | Push-button |
| [In] rated current | 80 A |
| Thermal protection adjustment range | 56...80 A |

| | |
|---|--|
| Magnetic tripping current | 1040 A |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Ui] rated insulation voltage | 690 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Ith] conventional free air thermal current | 80 A conforming to IEC 60947-4-1 |
| [Uimp] rated impulse withstand voltage | IEC 60947-2 6 kV |
| Power dissipation per pole | 8 W |
| Mechanical durability | 30000 cycles |
| Electrical durability | 30000 cycles for AC-3 at 440 V |
| Maximum operating rate | 25 cyc/h |
| Rated duty | Continuous conforming to IEC 60947-4-1 |
| Connections - terminals | Screw clamp terminals 1 cable(s) 2.5...35 mm ² solid Screw clamp terminals 1 cable(s) 2.5...16 mm ² flexible without cable end Screw clamp terminals 1 cable(s) 2.5...16 mm ² flexible with cable end |
| Tightening torque | 5 N.m on screw clamp terminals |
| Phase failure sensitivity | Yes conforming to IEC 60947-4-1 |
| Height | 120 mm |
| Width | 61.2 mm |
| Depth | 113 mm |
| Net weight | 0.7 kg |

Environment

| | |
|---------------------------------------|--|
| Standards | EN/IEC 60947-2 EN/IEC 60947-4-1 CSA C22.2 No 60947-4-1 UL 60947-4-1 |
| Product certifications | UL CSA LROS (Lloyds register of shipping) |
| Protective treatment | TC |
| IP degree of protection | IP20 conforming to IEC 60529 |
| IK degree of protection | IK04 |
| Ambient air temperature for operation | -20...60 °C |
| Ambient air temperature for storage | -40...80 °C |
| Fire resistance | 960 °C conforming to IEC 60695-2-1 |
| Operating altitude | 3000 m |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| EU RoHS Directive | Under investigation |
| Mercury free | Yes |
| RoHS exemption information | |
| China RoHS Regulation | |
| Environmental Disclosure | |
| Circularity Profile | No need of specific recycling operations |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

GV3ME80 is replaced by:



Thermal-magnetic motor circuit breakers GV3P73

Motor circuit breaker, TeSys GV3, 3P, 62-73 A, thermal magnetic, EverLink terminals

Qty 1

Reason for Substitution: End of life | Substitution date: 15 April 2019