

| Item | Partnumber             | Description                                                                                                                                                                                                                                                                                                                                                         |
|------|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1    | 3WL1106-2CB32-1AA2     | fixed-mounted circuit breaker 3-pole, size I, IEC In=630A to 690V, AC50/60Hz Icu=55kA at 500V rear connection horizontal Overcurrent release ETU 25 LSI protection adjustable 0.4-1 in With manual operating mechanism with storage with mechanical request without 1st auxiliary release without 2nd auxiliary release 2NO +2NC                                    |
| 2    | 3WL1108-2CB32-1AA2     | fixed-mounted circuit breaker 3-pole, size I, IEC In=800A to 690V, AC50/60Hz Icu=55kA at 500V rear connection horizontal                                                                                                                                                                                                                                            |
| 3    | 3WL1110-2CB32-1AA2     | fixed-mount non-aut. circuit-b. 3-pole, size I, IEC In=1000A to 690V, AC50/60Hz Icu=55kA at 500V rear connection horizontal without overcurrent release With manual operating mechanism with storage with mechanical request With 1st auxiliary release Shunt release "F", F1 50/60 Hz 230 V AC/220 V DC, 100% on-load factor without 2nd auxiliary release 2NO+2NC |
| 4    | 3WL1112-2CB32-1AA2     | fixed-mounted circuit breaker 3-pole, size I, IEC In=1250A to 690V, AC50/60Hz Icu=55kA at 500V rear connection horizontal                                                                                                                                                                                                                                           |
| 5    | 3WL1116-2<br>CB32-1AA2 | fixed-mounted circuit breaker 3-pole, size I, IEC In=1600A to 690V, AC50/60Hz Icu=55kA at 500V rear connection horizontal Overcurrent release ETU 25 LSI protection adjustable 0.4-1 in With manual operating mechanism with storage with mechanical request without 1st auxiliary release without 2nd auxiliary release 2NO +2NC                                   |
| 6    | 3WL1120-2CB32-1AA2     | fixed-mounted circuit breaker 3-pole, size I, IEC In=2000A to 690V, AC50/60Hz Icu=55kA at 500V rear connection horizontal                                                                                                                                                                                                                                           |
| 7    | 3WL1106-3CB32-1AA2     | fixed-mounted circuit breaker 3-pole, size I, IEC In=630A to 690V, AC50/60Hz Icu=66kA at 500V rear connection horizontal                                                                                                                                                                                                                                            |
| 8    | 3WL1108-3CB32-1AA2     | FIXED-MOUNTED CIRCUIT BREAKER 3-POLE, SIZE I, IEC IN=800A TO 690V, AC50/60HZ ICU=66KA AT 500V REAR CONNECTION HORIZONTAL                                                                                                                                                                                                                                            |
| 9    | 3WL1110-3CB32-1AA2     | fixed-mounted circuit breaker 3-pole, size I, IEC In=1000A to 690V, AC50/60Hz Icu=66kA at 500V rear connection horizontal                                                                                                                                                                                                                                           |
| 10   | 3WL1112-3CB32-1AA2     | INTERRUPTOR DE MONTAJE FIJO 3 POLOS, TAMAÑO I, IEC IN=1250A HASTA 690V, AC50/60HZ ICU=66KA CON 500V CONEX. POSTERIOR HORIZONTAL                                                                                                                                                                                                                                     |
| 11   | 3WL1116-3CB32-1AA2     | fixed-mounted circuit breaker 3-pole, size I, IEC In=1600A to 690V, AC50/60Hz Icu=66kA at 500V rear connection horizontal                                                                                                                                                                                                                                           |
| 12   | 3WL1120-3DG32-1AA2     | FIXED-MOUNTED CIRCUIT BREAKER 3-POLE, SIZE I, IEC IN=2000A TO 690V, AC50/60HZ ICU=66KA AT 500V REAR CONNECTION HORIZONTAL                                                                                                                                                                                                                                           |
| 13   | 3WL1225-2CB32-1AA2     | FIXED-MOUNTED CIRCUIT BREAKER 3-POLE, SIZE II, IEC IN=2500A TO 690V, AC50/60HZ ICU=66KA AT 500V REAR CONNECTION HORIZONTAL                                                                                                                                                                                                                                          |
| 14   | 3WL1232-2CB32-1AA2     | fixed-mounted circuit breaker 3-pole, size II, IEC In=3200A to 690V, AC50/60Hz Icu=66kA at 500V rear connection horizontal                                                                                                                                                                                                                                          |
| 15   | 3WL1240-2CB31-1AA2     | FIXED-MOUNTED CIRCUIT BREAKER 3-POLE, SIZE II, IEC IN=4000A TO 690V, AC50/60HZ ICU=66KA AT 500V REAR CONNECTION VERTICAL                                                                                                                                                                                                                                            |
| 16   | 3WL1106-2CB36-1AA2     | withdrawable circuit breaker with guide frame 3-pole, size I, IEC In=630A to 690V, AC50/60Hz Icu=55kA at 500V rear connection horizontal                                                                                                                                                                                                                            |
| 17   | 3WL1108-2CB<br>36-1AA2 | withdrawable circuit breaker with guide frame 3-pole, size I, IEC In=800A to 690V, AC50/60Hz Icu=55kA at 500V rear connection horizontal                                                                                                                                                                                                                            |
| 18   | 3WL1110-2CB36-1AA2     | withdrawable circuit breaker with guide frame 3-pole, size I, IEC In=1000A to 690V, AC50/60Hz Icu=55kA at 500V rear connection horizontal                                                                                                                                                                                                                           |
| 19   | 3WL1112-2CB36-1AA2     | WITHDRAWABLE CIRCUIT BREAKER WITH GUIDE FRAME 3-POLE, SIZE I, IEC IN=1600A TO 690V, AC50/60HZ ICU=55KA AT 500V REAR CONNECTION HORIZONTAL                                                                                                                                                                                                                           |
| 20   | 3WL1120-2<br>CB36-1AA2 | withdrawable circuit breaker with guide frame 3-pole, size I, IEC In=2000A to 690V, AC50/60Hz Icu=55kA at 500V rear connection horizontal                                                                                                                                                                                                                           |
| 21   | 3WL1106-3<br>DG36-1AA2 | withdrawable circuit breaker with guide frame 3-pole, size I, IEC In=630A to 690V, AC50/60Hz Icu=66kA at 500V rear connection horizontal                                                                                                                                                                                                                            |
| 22   | 3WL1108-3DG36-1AA2     | withdrawable circuit breaker with guide frame 3-pole, size I, IEC In=800A to 690V,                                                                                                                                                                                                                                                                                  |

| Item | Partnumber         | Description                                                                                                                                                                                        |
|------|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 23   | 3WL1110-3DG36-1AA2 | AC50/60Hz Icu=66kA at 500V rear connection horizontal<br>withdrawable circuit breaker with guide frame 3-pole, size I, IEC In=1000A to 690V, AC50/60Hz Icu=66kA at 500V rear connection horizontal |
| 24   | 3WL1112-3DG36-1AA2 | withdrawable circuit breaker with guide frame 3-pole, size i, IEC In=1250A to 690V, AC50/60Hz Icu=66kA at 500V rear connection horizontal                                                          |
| 25   | 3WL1116-3DG36-1AA2 | withdrawable circuit breaker with guide frame 3-pole, size I, IEC In=1600A to 690V, AC50/60Hz Icu=66kA at 500V rear connection horizontal                                                          |
| 26   | 3WL1120-3DG36-1AA2 | WITHDRAWABLE CIRCUIT BREAKER WITH GUIDE FRAME 3-POLE, SIZE I, IEC IN=2000A TO 690V, AC50/60HZ ICU=66KA AT 500V REAR CONNECTION HORIZONTAL                                                          |
| 27   | 3WL1225-2CB36-1AA2 | withdrawable circuit breaker with guide frame 3-pole, size II, IEC In=2500A to 690V, AC50/60Hz Icu=66kA at 500V rear connection horizontal                                                         |
| 28   | 3WL1232-2CB36-1AA2 | withdrawable circuit breaker with guide frame 3-pole, size II, IEC In=3200A to 690V, AC50/60Hz Icu=66kA at 500V rear connection horizontal                                                         |
| 29   | 3WL1240-2DG37-1AA2 | WITHDRAW. NON-AUT. CIRCUIT-B. WITH GUIDE FRAME 3-POLE, SIZE II, IEC IN=4000A TO 690V, AC50/60HZ ICU=66KA AT 500V REAR CONNECTION VERTICAL                                                          |
| 30   | 3WL1106-4DG32-1AA2 | fixed-mounted circuit breaker 3-pole, size I, IEC In=630A to 690V, AC50/60Hz Icu=85kA at 500V rear connection horizontal                                                                           |
| 31   | 3WL1108-4DG32-1AA2 | fixed-mounted circuit breaker 3-pole, size I, IEC In=800A to 690V, AC50/60Hz Icu=85kA at 500V rear connection horizontal                                                                           |
| 32   | 3WL1110-4DG32-1AA2 | Siemens FIXED-MOUNTED CIRCUIT BREAKER 3-POLE, SIZE I, IEC IN=1000A TO 690V, AC50/60HZ ICU=85KA AT 500V REAR CONNECTION HORIZONTAL                                                                  |
| 33   | 3WL1112-4DG32-1AA2 | fixed-mounted circuit breaker 3-pole, size I, IEC In=1250A to 690V, AC50/60Hz Icu=85kA at 500V rear connection horizontal                                                                          |
| 34   | 3WL1116-4DG32-1AA2 | fixed-mounted circuit breaker 3-pole, size I, IEC In=1600A to 690V, AC50/60Hz Icu=85kA at 500V rear connection horizontal                                                                          |
| 35   | 3WL1120-4DG32-1AA2 | FIXED-MOUNTED CIRCUIT BREAKER 3-POLE, SIZE I, IEC IN=2000A TO 690V, AC50/60HZ ICU=85KA AT 500V REAR CONNECTION HORIZONTAL                                                                          |
| 36   | 3WL1225-3DG32-1AA2 | fixed-mounted circuit breaker 3-pole, size II, IEC In=2500A to 690V, AC50/60Hz Icu=80kA at 500V rear connection horizontal                                                                         |
| 37   | 3WL1232-3DG32-1AA2 | fixed-mounted circuit breaker 3-pole, size ii, iec in=3200a to 690v, ac50/60hz icu=80ka at 500v rear connection horizontal                                                                         |
| 38   | 3WL1240-3DG31-1AA2 | fixed-mounted circuit breaker 3-pole, size II, IEC In=4000A to 690V, AC50/60Hz Icu=80kA at 500V rear connection vertical                                                                           |
| 39   | 3WL1208-4DG32-1AA2 | fixed-mounted circuit breaker 3-pole, size II, IEC In=800A to 690V, AC50/60Hz Icu=100kA at 500V rear connection horizontal                                                                         |
| 40   | 3WL1210-4DG32-1AA2 | fixed-mounted circuit breaker 3-pole, size II, IEC In=1000A to 690V, AC50/60Hz Icu=100kA at 500V rear connection horizontal                                                                        |
| 41   | 3WL1212-4DG32-1AA2 | fixed-mounted circuit breaker 3-pole, size II, IEC In=1250A to 690V, AC50/60Hz Icu=100kA at 500V rear connection horizontal                                                                        |
| 42   | 3WL1216-4DG32-1AA2 | fixed-mounted circuit breaker 3-pole, size II, IEC In=1600A to 690V, AC50/60Hz Icu=100kA at 500V rear connection horizontal                                                                        |
| 43   | 3WL1220-4DG32-1AA2 | FIXED-MOUNTED CIRCUIT BREAKER 3-POLE, SIZE II, IEC IN=2000A TO 690V, AC50/60HZ ICU=100KA AT 500V REAR CONNECTION HORIZONTAL                                                                        |
| 44   | 3WL1225-4DG32-1AA2 | fixed-mounted circuit breaker 3-pole, size II, IEC In=2500A to 690V, AC50/60Hz Icu=100kA at 500V rear connection horizontal                                                                        |
| 45   | 3WL1232-4DG32-1AA2 | fixed-mounted circuit breaker 3-pole, size II, IEC In=3200A to 690V, AC50/60Hz Icu=100kA at 500V rear connection horizontal                                                                        |
| 46   | 3WL1240-4DG31-1AA2 | fixed-mounted circuit breaker 3-pole, size II, IEC In=4000A to 690V, AC50/60Hz Icu=100kA at 500V rear connection vertical                                                                          |
| 47   | 3WL1340-4DG32-1AA2 | FIXED-MOUNTED CIRCUIT BREAKER 3-POLE, SIZE III, IEC IN=4000A TO 690V, AC50/60HZ ICU=100KA AT 500V REAR CONNECTION HORIZONTAL                                                                       |
| 48   | 3WL1350-4DG32-1AA2 | fixed-mounted circuit breaker 3-pole, size III, IEC In=5000A to 690V, AC50/60Hz Icu=100kA at 500V rear connection horizontal                                                                       |

| Item | Partnumber         | Description                                                                                                                                   |
|------|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| 49   | 3WL1363-4DG31-1AA2 | fixed-mounted circuit breaker 3-pole, size III, IEC In=6300A to 690V, AC50/60Hz Icu=100kA at 500V rear connection vertical,                   |
| 50   | 3WL1106-4CB36-1AA2 | withdrawable circuit breaker with guide frame 3-pole, size I, IEC In=630A to 690V, AC50/60Hz Icu=85kA at 500V rear connection horizontal      |
| 51   | 3WL1108-4CB36-1AA2 | withdrawable circuit breaker with guide frame 3-pole, size I, IEC In=800A to 690V, AC50/60Hz Icu=85kA at 500V rear connection horizontal      |
| 52   | 3WL1110-4CB36-1AA2 |                                                                                                                                               |
| 53   | 3WL1112-4CB36-1AA2 | withdrawable circuit breaker with guide frame 3-pole, size I, IEC In=1250A to 690V, AC50/60Hz Icu=85kA at 500V rear connection horizontal     |
| 54   | 3WL1116-4CB36-1AA2 | withdrawable circuit breaker with guide frame 3-pole, size I, IEC In=1600A to 690V, AC50/60Hz Icu=85kA at 500V rear connection horizontal     |
| 55   | 3WL1120-4CB6-1AA2  | withdrawable circuit breaker with guide frame 3-pole, size I, IEC In=2000A to 690V, AC50/60Hz Icu=85kA at 500V rear connection horizontal     |
| 56   | 3WL1225-3CB36-1AA2 | withdrawable circuit breaker with guide frame 3-pole, size II, IEC In=2500A to 690V, AC50/60Hz Icu=80kA at 500V rear connection horizontal    |
| 57   | 3WL1232-3CB36-1AA2 | withdrawable circuit breaker with guide frame 3-pole, size II, IEC In=3200A to 690V, AC50/60Hz Icu=80kA at 500V rear connection horizontal    |
| 58   | 3WL1240-3CB37-1AA2 | WITHDRAWABLE CIRCUIT BREAKER WITH GUIDE FRAME 3-POLE, SIZE II, IEC IN=4000A TO 690V, AC50/60HZ ICU=80KA AT 500V REAR CONNECTION VERTICAL      |
| 59   | 3WL1208-4CB36-1AA2 | withdrawable circuit breaker with guide frame 3-pole, size II, IEC In=800A to 690V, AC50/60Hz Icu=100kA at 500V rear connection horizontal    |
| 60   | 3WL1210-4CB36-1AA2 | withdrawable circuit breaker with guide frame 3-pole, size II, IEC In=1000A to 690V, AC50/60Hz Icu=100kA at 500V rear connection horizontal   |
| 61   | 3WL1212-4CB36-1AA2 | withdrawable circuit breaker with guide frame 3-pole, size II, IEC In=1250A to 690V, AC50/60Hz Icu=100kA at 500V rear connection horizontal   |
| 62   | 3WL1216-4CB36-1AA2 | withdrawable circuit breaker with guide frame 3-pole, size II, IEC In=1600A to 690V, AC50/60Hz Icu=100kA at 500V rear connection horizontal   |
| 63   | 3WL1220-4CB36-1AA2 | withdrawable circuit breaker with guide frame 3-pole, size II, IEC In=2000A to 690V, AC50/60Hz Icu=100kA at 500V rear connection horizontal   |
| 64   | 3WL1225-4CB36-1AA2 | withdrawable circuit breaker with guide frame 3-pole, size II, IEC In=2500A to 690V, AC50/60Hz Icu=100kA at 500V rear connection horizontal   |
| 65   | 3WL1232-4CB36-1AA2 | WITHDRAWABLE CIRCUIT BREAKER WITH GUIDE FRAME 3-POLE, SIZE II, IEC IN=3200A TO 690V, AC50/60HZ ICU=100KA AT 500V REAR CONNECTION HORIZONTAL   |
| 66   | 3WL1240-4CB37-1AA2 | withdrawable circuit breaker with guide frame 3-pole, size II, IEC In=4000A to 690V, AC50/60Hz Icu=100kA at 500V rear connection vertical     |
| 67   | 3WL1340-4DG36-1AA2 | WITHDRAW. NON-AUT. CIRCUIT-B. WITH GUIDE FRAME 3-POLE, SIZE III, IEC IN=4000A TO 690V, AC50/60HZ ICU=100KA AT 500V REAR CONNECTION HORIZONTAL |
| 68   | 3WL1350-4DG36-1AA2 | withdrawable circuit breaker with guide frame 3-pole, size iii, IEC In=5000A to 690V, AC50/60Hz Icu=100kA at 500V rear connection horizontal  |
| 69   | 3WL1363-4DG37-1AA2 | withdrawable circuit breaker with guide frame 3-pole, size III, IEC In=6300A to 690V, AC50/60Hz Icu=100kA at 500V rear connection vertical    |
| 70   | 3WL1106-2DG42-1AA2 | FIXED-MOUNTED CIRCUIT BREAKER 4-POLE, SIZE I, IEC IN=630A TO 690V, AC50/60HZ ICU=55KA AT 500V REAR CONNECTION HORIZONTAL                      |
| 71   | 3WL1108-2DG42-1AA2 | fixed-mounted circuit breaker 4-pole, size I, IEC In=800A to 690V, AC50/60Hz Icu=55kA at 500V rear connection horizontal                      |
| 72   | 3WL1110-2DG42-1AA2 | fixed-mounted circuit breaker 4-pole, size I, IEC In=1000A to 690V, AC50/60Hz Icu=55kA at 500V rear connection horizontal                     |
| 73   | 3WL1112-2DG42-1AA2 | FIXED-MOUNTED CIRCUIT BREAKER 4-POLE, SIZE I, IEC IN=1250A TO 690V, AC50/60HZ ICU=55KA AT 500V REAR CONNECTION HORIZONTAL                     |
| 74   | 3WL1116-2DG42-1AA2 | fixed-mounted circuit breaker 4-pole, size I, IEC In=1600A to 690V, AC50/60Hz Icu=55kA at 500V rear connection horizontal                     |
| 75   | 3WL1120-2DG42-1AA2 | fixed-mounted circuit breaker 4-pole, size I, IEC In=2000A to 690V, AC50/60Hz                                                                 |

| Item | Partnumber         | Description                                                                                                                                                            |
|------|--------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|      |                    | Icu=55kA at 500V rear connection horizontal                                                                                                                            |
| 76   | 3WL1106-3DG42-1AA2 | fixed-mounted circuit breaker 4-pole, size I, IEC In=630A to 690V, AC50/60Hz<br>Icu=66kA at 500V rear connection horizontal                                            |
| 77   | 3WL1108-3DG42-1AA2 | fixed-mounted circuit breaker 4-pole, size I, IEC In=800A to 690V, AC50/60Hz<br>Icu=66kA at 500V rear connection horizontal                                            |
| 78   | 3WL1110-3DG42-1AA2 | fixed-mounted circuit breaker 4-pole, size I, IEC In=1000A to 690V, AC50/60Hz<br>Icu=66kA at 500V rear connection horizontal                                           |
| 79   | 3WL1112-3DG42-1AA2 | fixed-mounted circuit breaker 4-pole, size I, IEC In=1250A to 690V, AC50/60Hz<br>Icu=66kA at 500V rear connection horizontal                                           |
| 80   | 3WL1116-3DG42-1AA2 | fixed-mounted circuit breaker 4-pole, size I, IEC In=1600A to 690V, AC50/60Hz<br>Icu=66kA at 500V rear connection horizontal                                           |
| 81   | 3WL1120-3DG42-1AA2 | fixed-mounted circuit breaker 4-pole, size I, IEC In=2000A to 690V, AC50/60Hz<br>Icu=66kA at 500V rear connection horizontal                                           |
| 82   | 3WL1225-2DG42-1AA2 | fixed-mounted circuit breaker 4-pole, size II, IEC In=2500A to 690V, AC50/60Hz<br>Icu=66kA at 500V rear connection horizontal                                          |
| 83   | 3WL1232-2DG42-1AA2 | fixed-mounted circuit breaker 4-pole, size II, IEC In=3200A to 690V, AC50/60Hz<br>Icu=66kA at 500V rear connection horizontal                                          |
| 84   | 3WL1240-2DG41-1AA2 | FIXED-MOUNTED CIRCUIT BREAKER 4-POLE, SIZE II, IEC IN=4000A TO 690V,<br>AC50/60HZ ICU=66KA AT 500V REAR CONNECTION VERTICAL                                            |
| 85   | 3WL1106-2DG46-1AA2 | withdrawable circuit breaker with guide frame 4-pole, size I, IEC In=630A to 690V,<br>AC50/60Hz Icu=55kA at 500V rear connection horizontal                            |
| 86   | 3WL1108-2DG46-1AA2 | withdrawable circuit breaker with guide frame 4-pole, size I, IEC In=800A to 690V,<br>AC50/60Hz Icu=55kA at 500V rear connection horizontal                            |
| 87   | 3WL1110-2DG46-1AA2 | withdrawable circuit breaker with guide frame 4-pole, size I, IEC In=1000A to 690V,<br>AC50/60Hz Icu=55kA at 500V rear connection horizontal                           |
| 88   | 3WL1112-2DG46-1AA2 | withdrawable circuit breaker with guide frame 4-pole, size I, IEC In=1250A to 690V,<br>AC50/60Hz Icu=55kA at 500V rear connection horizontal                           |
| 89   | 3WL1116-2DG46-1AA2 | withdrawable circuit breaker with guide frame 4-pole, size I, IEC In=1600A to 690V,<br>AC50/60Hz Icu=55kA at 500V rear connection horizontal                           |
| 90   | 3WL1120-2DG46-1AA2 | withdrawable circuit breaker with guide frame 4-pole, size I, IEC In=2000A to 690V,<br>AC50/60Hz Icu=55kA at 500V rear connection horizontal                           |
| 91   | 3WL1106-3DG46-1AA2 | withdrawable circuit breaker with guide frame 4-pole, size I, IEC In=630A to 690V,<br>AC50/60Hz Icu=66kA at 500V rear connection horizontal                            |
| 92   | 3WL1108-3DG46-1AA2 | withdrawable circuit breaker with guide frame 4-pole, size I, IEC In=800A to 690V,<br>AC50/60Hz Icu=66kA at 500V rear connection horizontal                            |
| 93   | 3WL1110-3DG46-1AA2 | withdrawable circuit breaker with guide frame 4-pole, size I, IEC In=1000A to 690V,<br>AC50/60Hz Icu=66kA at 500V rear connection horizontal                           |
| 94   | 3WL1112-3DG46-1AA2 | withdrawable circuit breaker with guide frame 4-pole, size I, IEC In=1250A to 690V,<br>AC50/60Hz Icu=66kA at 500V rear connection horizontal                           |
| 95   | 3WL1116-3DG46-1AA2 | withdrawable circuit breaker with guide frame 4-pole, size I, IEC In=1600A to 690V,<br>AC50/60Hz Icu=66kA at 500V rear connection horizontal                           |
| 96   | 3WL1120-3DG46-1AA2 | withdrawable circuit breaker with guide frame 4-pole, size I, IEC In=2000A to 690V,<br>AC50/60Hz Icu=66kA at 500V rear connection horizontal                           |
| 97   | 3WL1225-2DG46-1AA2 | withdrawable circuit breaker with guide frame 4-pole, size II, IEC In=2500A to 690V,<br>AC50/60Hz Icu=66kA at 500V rear connection horizontal                          |
| 98   | 3WL1232-2DG46-1AA2 | withdrawable circuit breaker with guide frame 4-pole, size II, IEC In=3200A to 690V,<br>AC50/60Hz Icu=66kA at 500V rear connection horizontal                          |
| 99   | 3WL1240-2DG47-1AA2 | Siemens 3WL1240-2..47-.... withdrawable circuit breaker with guide frame 4-pole,<br>size ii, iec in=4000a to 690v, ac50/60hz icu=66ka at 500v rear connection vertical |
| 100  | 3WL1106-4DG42-1AA2 | fixed-mounted circuit breaker 4-pole, size I, IEC In=630A to 690V, AC50/60Hz<br>Icu=85kA at 500V rear connection horizontal                                            |
| 101  | 3WL1108-4DG42-1AA2 | fixed-mounted circuit breaker 4-pole, size I, IEC In=800A to 690V, AC50/60Hz<br>Icu=85kA at 500V rear connection horizontal                                            |
| 102  | 3WL1110-4DG42-1AA2 | FIXED-MOUNTED CIRCUIT BREAKER 4-POLE, SIZE I, IEC IN=1000A TO 690V,                                                                                                    |

| Item | Partnumber         | Description                                                                                                                                              |
|------|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
|      |                    | AC50/60HZ ICU=85KA AT 500V REAR CONNECTION HORIZONTAL                                                                                                    |
| 103  | 3WL1116-4DG42-1AA2 | fixed-mounted circuit breaker 4-pole, size I, IEC In=1600A to 690V, AC50/60Hz Icu=85kA at 500V rear connection horizontal                                |
| 104  | 3WL1120-4DG42-1AA2 | FIXED-MOUNTED CIRCUIT BREAKER 4-POLE, SIZE I, IEC IN=2000A TO 690V, AC50/60HZ ICU=85KA AT 500V REAR CONNECTION HORIZONTAL                                |
| 105  | 3WL1225-3DG42-1AA2 | fixed-mounted circuit breaker 4-pole, size II, IEC In=2500A to 690V, AC50/60Hz Icu=80kA at 500V rear connection horizontal                               |
| 106  | 3WL1232-3DG42-1AA2 | fixed-mounted circuit breaker 4-pole, size II, IEC In=3200A to 690V, AC50/60Hz Icu=80kA at 500V rear connection horizontal                               |
| 107  | 3WL1240-3DG41-1AA2 | fixed-mounted circuit breaker 4-pole, size II, IEC In=4000A to 690V, AC50/60Hz Icu=80kA at 500V rear connection vertical                                 |
| 108  | 3WL1208-4DG42-1AA2 | fixed-mounted circuit breaker 4-pole, size II, IEC In=800A to 690V, AC50/60Hz Icu=100kA at 500V rear connection horizontal                               |
| 109  | 3WL1210-4DG42-1AA2 | fixed-mounted circuit breaker 4-pole, size II, IEC In=1000A to 690V, AC50/60Hz Icu=100kA at 500V rear connection horizontal                              |
| 110  | 3WL1212-4DG42-1AA2 | fixed-mounted circuit breaker 4-pole, size II, IEC In=1250A to 690V, AC50/60Hz Icu=100kA at 500V rear connection horizontal                              |
| 111  | 3WL1216-4DG42-1AA2 | fixed-mounted circuit breaker 4-pole, size II, IEC In=1600A to 690V, AC50/60Hz Icu=100kA at 500V rear connection horizontal                              |
| 112  | 3WL1220-4DG42-1AA2 | FIXED-MOUNTED CIRCUIT BREAKER 4-POLE, SIZE II, IEC IN=2000A TO 690V, AC50/60HZ ICU=100KA AT 500V REAR CONNECTION HORIZONTAL                              |
| 113  | 3WL1225-4DG42-1AA2 | Siemens 3WL1225-4A.42-.... fixed-mount non-aut. circuit-b. 4-pole, size ii, iec in=2500a to 690v, ac50/60hz icu=100ka at 500v rear connection horizontal |
| 114  | 3WL1232-4DG42-1AA2 | fixed-mounted circuit breaker 4-pole, size II, IEC In=3200A to 690V, AC50/60Hz Icu=100kA at 500V rear connection horizontal                              |
| 115  | 3WL1240-4DG41-1AA2 | FIXED-MOUNTED CIRCUIT BREAKER 4-POLE, SIZE II, IEC IN=4000A TO 690V, AC50/60HZ ICU=100KA AT 500V REAR CONNECTION VERTICAL                                |
| 116  | 3WL1340-4DG42-1AA2 | FIXED-MOUNTED CIRCUIT BREAKER 4-POLE, SIZE III, IEC IN=4000A TO 690V, AC50/60HZ ICU=100KA AT 500V REAR CONNECTION HORIZONTAL                             |
| 117  | 3WL1350-4DG42-1AA2 | fixed-mounted circuit breaker 4-pole, size III, IEC In=5000A to 690V, AC50/60Hz Icu=100kA at 500V rear connection horizontal                             |
| 118  | 3WL1363-4DG41-1AA2 | FIXED-MOUNTED CIRCUIT BREAKER 4-POLE, SIZE III, IEC IN=6300A TO 690V, AC50/60HZ ICU=100KA AT 500V REAR CONNECTION VERTICAL,                              |
| 119  | 3WL1106-4DG46-1AA2 | withdrawable circuit breaker with guide frame 4-pole, size I, IEC In=630A to 690V, AC50/60Hz Icu=85kA at 500V rear connection horizontal                 |
| 120  | 3WL1108-4DG46-1AA2 | withdrawable circuit breaker with guide frame 4-pole, size I, IEC In=800A to 690V, AC50/60Hz Icu=85kA at 500V rear connection horizontal                 |
| 121  | 3WL1110-4DG46-1AA2 | withdrawable circuit breaker with guide frame 4-pole, size I, IEC In=1000A to 690V, AC50/60Hz Icu=85kA at 500V rear connection horizontal                |
| 122  | 3WL1112-4DG46-1AA2 | withdrawable circuit breaker with guide frame 4-pole, size I, IEC In=1250A to 690V, AC50/60Hz Icu=85kA at 500V rear connection horizontal                |
| 123  | 3WL1116-4DG46-1AA2 | withdrawable circuit breaker with guide frame 4-pole, size I, IEC In=1600A to 690V, AC50/60Hz Icu=85kA at 500V rear connection horizontal                |
| 124  | 3WL1120-4DG46-1AA2 | withdrawable circuit breaker with guide frame 4-pole, size I, IEC In=2000A to 690V, AC50/60Hz Icu=85kA at 500V rear connection horizontal                |
| 125  | 3WL1225-3DG46-1AA2 | withdrawable circuit breaker with guide frame 4-pole, size II, IEC In=2500A to 690V, AC50/60Hz Icu=80kA at 500V rear connection horizontal               |
| 126  | 3WL1232-3DG46-1AA2 | withdrawable circuit breaker with guide frame 4-pole, size II, IEC In=3200A to 690V, AC50/60Hz Icu=80kA at 500V rear connection horizontal               |
| 127  | 3WL1240-3DG47-1AA2 | withdrawable circuit breaker with guide frame 4-pole, size II, IEC In=4000A to 690V, AC50/60Hz Icu=80kA at 500V rear connection vertical                 |
| 128  | 3WL1208-4DG46-1AA2 | withdrawable circuit breaker with guide frame 4-pole, size II, IEC In=800A to 690V, AC50/60Hz Icu=100kA at 500V rear connection horizontal               |
| 129  | 3WL1210-4DG46-1AA2 | withdrawable circuit breaker with guide frame 4-pole, size II, IEC In=1000A to 690V,                                                                     |

| Item | Partnumber         | Description                                                                                                                                  |
|------|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
|      |                    | AC50/60Hz Icu=100kA at 500V rear connection horizontal                                                                                       |
| 130  | 3WL1212-4DG46-1AA2 | WITHDRAWABLE CIRCUIT BREAKER WITH GUIDE FRAME 4-POLE, SIZE II, IEC IN=1250A TO 690V, AC50/60HZ ICU=100KA AT 500V REAR CONNECTION HORIZONTAL  |
| 131  | 3WL1216-4DG46-1AA2 | withdrawable circuit breaker with guide frame 4-pole, size II, IEC In=1600A to 690V, AC50/60Hz Icu=100kA at 500V rear connection horizontal  |
| 132  | 3WL1220-4DG46-1AA2 | WITHDRAWABLE CIRCUIT BREAKER WITH GUIDE FRAME 4-POLE, SIZE II, IEC IN=2000A TO 690V, AC50/60HZ ICU=100KA AT 500V REAR CONNECTION HORIZONTAL  |
| 133  | 3WL1225-4DG46-1AA2 | WITHDRAWABLE CIRCUIT BREAKER WITH GUIDE FRAME 4-POLE, SIZE II, IEC IN=2500A TO 690V, AC50/60HZ ICU=100KA AT 500V REAR CONNECTION HORIZONTAL  |
| 134  | 3WL1232-4DG46-1AA2 | WITHDRAWABLE CIRCUIT BREAKER WITH GUIDE FRAME 4-POLE, SIZE II, IEC IN=3200A TO 690V, AC50/60HZ ICU=100KA AT 500V REAR CONNECTION HORIZONTAL  |
| 135  | 3WL1240-4DG47-1AA2 | WITHDRAW. NON-AUT. CIRCUIT-B. WITH GUIDE FRAME 4-POLE, SIZE II, IEC IN=4000A TO 690V, AC50/60HZ ICU=100KA AT 500V REAR CONNECTION VERTICAL   |
| 136  | 3WL1340-4DG46-1AA2 | WITHDRAWABLE CIRCUIT BREAKER WITH GUIDE FRAME 4-POLE, SIZE III, IEC IN=4000A TO 690V, AC50/60HZ ICU=100KA AT 500V REAR CONNECTION HORIZONTAL |
| 137  | 3WL1350-4DG46-1AA2 | WITHDRAWABLE CIRCUIT BREAKER WITH GUIDE FRAME 4-POLE, SIZE III, IEC IN=5000A TO 690V, AC50/60HZ ICU=100KA AT 500V REAR CONNECTION HORIZONTAL |
| 138  | 3WL1363-4DG47-1AA2 | WITHDRAWABLE CIRCUIT BREAKER WITH GUIDE FRAME 4-POLE, SIZE III, IEC IN=6300A TO 690V, AC50/60HZ ICU=100KA AT 500V REAR CONNECTION VERTICAL   |
| 139  | 3WL9111-0AF04-0AA0 | accessories circuit breaker 3WL motor drive AC 50/60Hz 208-240V/DC 220-250                                                                   |
| 140  | 3WL9111-0AF03-0AA0 | accessories circuit breaker 3WL motor drive AC 50/60Hz 110-125v/dC110-127V                                                                   |
| 141  | 3WL9111-0AD06-0AA0 | accessories circuit breaker 3WL shunt trip AC 50/60Hz 208-240V/ DC 220V 100% ed                                                              |
| 142  | 3WL9111-0AD05-0AA0 | accessories circuit breaker 3WL shunt trip AC 50/60Hz 110V/ DC 110V 100% ed                                                                  |
| 143  | 3WL9111-0AE05-0AA0 | accessories circuit breaker 3WL undervoltage release, Instant. instantaneous AC 50/60Hz 208-240V/DC 220-250V                                 |
| 144  | 3WL9111-0AE06-0AA0 | accessories circuit breaker 3WL undervoltage release, non-del. AC 50/60Hz 380-415V                                                           |
| 145  | 3WL9111-0AE13-0AA0 | accessories circuit breaker 3WL undervoltage release, w.delay AC 50/60Hz 208-240V/DC 220-250V                                                |
| 146  | 3WL9111-0AE14-0AA0 | accessories circuit breaker 3WL undervoltage release, w.delay AC 50/60Hz 380-415V                                                            |
| 147  | 3WL9111-0AJ02-0AA0 | Siemens 3WL9111-0AJ02-0AA0 available at EU Automation. Get in touch today for a quick price.                                                 |
| 148  | 3WL9111-0AG01-0AA0 | accessories circuit breaker 3WL aux.switch block 2NO +2NC                                                                                    |
| 149  | 3WL9111-0AB01-0AA0 | accessories circuit breaker 3WL knife strip                                                                                                  |
| 150  | 3WL9111-0AB03-0AA0 | accessories circuit breaker 3WL manual plug sigut                                                                                            |
| 151  | 3WL9111-0AB07-0AA0 | accessories circuit breaker 3WL cod.set f. fixed-mount circ.br.                                                                              |
| 152  | 3WL9111-0AB08-0AA0 | accessories circuit breaker 3WL wiper contact module f. withdrawable circ.breaker                                                            |
| 153  | 3WL9111-0AB18-0AA0 | accessories circuit breaker 3WL wiper contact module f. withdrawable circ.breaker sigut                                                      |
| 154  | 3WL9111-0AH01-0AA0 | accessories circuit breaker 3WL ready to run message s20                                                                                     |
| 155  | 3WL9111-0AH14-0AA0 | accessories circuit breaker 3WL 1st trip signalling switch 1 CO; S24                                                                         |
| 156  | 3WL9111-0AH08-0AA0 | accessories circuit breaker 3WL signal switch for spring storage state                                                                       |
| 157  | 3WL9111-0AH07-0AA0 | accessories circuit breaker 3WL 5-digit mechanical operations counter                                                                        |

| Item | Partnumber         | Description                                                                                                                                                                                                                                |
|------|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 158  | 3WL9111-0AP01-0AA0 | accessories circuit breaker 3WL door sealing frame IP41 for inst. In contr.cabinet door                                                                                                                                                    |
| 159  | 3WL9211-1AC00-0AA1 | accessory for breaker 3WL guide frame size I 630-1000A design up to 66ka 3-pole, rear horizontal connection Without auxiliary plug connectors without auxiliary current plug connectors without position signaling switch without shutter  |
| 160  | 3WL9211-2AC00-0AA1 | accessory for breaker 3WL guide frame size I 1250-1600A design up to 66ka 3-pole, rear horizontal connection Without auxiliary plug connectors without auxiliary current plug connectors without position signaling switch without shutter |
| 161  | 3WL9211-3AC00-0AA1 | accessory for breaker 3WL guide frame size I 630-2000A design up to 85ka 3-pole, rear horizontal connection Without auxiliary plug connectors without auxiliary current plug connectors without position signaling switch without shutter  |
| 162  | 3WL9212-3AC00-0AA1 | Accessory f. breaker 3WL guide frame size II 2000A 3-pole, rear horizontal connection Without auxiliary plug connectors without auxiliary current plug connectors without position signaling switch without shutter                        |
| 163  | 3WL9212-4AC00-0AA1 | Accessory f. breaker 3WL guide frame size II 2500A 3-pole, rear horizontal connection Without auxiliary plug connectors without auxiliary current plug connectors without position signaling switch without shutter                        |
| 164  | 3WL9212-5AC00-0AA1 | Accessory f. breaker 3WL guide frame size II 3200A 3-pole, rear horizontal connection Without auxiliary plug connectors without auxiliary current plug connectors without position signaling switch without shutter                        |
| 165  | 3WL9213-6AC00-0AA1 | Accessory f. breaker 3WL guide frame size III 4000A 3-pole, rear horizontal connection Without auxiliary plug connectors without auxiliary current plug connectors without position signaling switch without shutter                       |
| 166  | 3WL9213-7AC00-0AA1 | Accessory f. breaker 3WL guide frame size III 5000A 3-pole, rear horizontal connection Without auxiliary plug connectors without auxiliary current plug connectors without position signaling switch without shutter                       |
| 167  | 3WL9213-8AD00-0AA1 | Accessory f. breaker 3WL guide frame size III 6300A 3-pole, rear vertical connection Without auxiliary plug connectors without auxiliary current plug connectors without position signaling switch without shutter                         |
| 168  | 3WL9111-0BC11-0AA0 | Siemens 3WL9111-0BC11-0AA0 accessories circuit-breaker 3wl kit for conv. fixed-mounted to withdrawable size 1 3-pole (aux.current shift modules & guide frames are to be ordered individually)                                             |
| 169  | 3WL9111-0BC12-0AA0 | accessories circuit-breaker 3WL kit for conv. fixed-mounted to withdrawable size 2 3-pole (aux.current shift modULes and guide frames are to be ordered individually)                                                                      |
| 170  | 3WL9111-0BC13-0AA0 | accessories circuit-breaker 3WL kit for conv. fixed-mounted to withdrawable size 3 3-pole (aux.current shift modULes and guide frames are to be ordered individually)                                                                      |
| 171  | 3WL9111-0AH11-0AA0 | accessories circuit breaker 3WL position signal switch f. guide frame, 1st block 3 micro-switches                                                                                                                                          |
| 172  | 3WL9111-0AH12-0AA0 | accessories circuit breaker 3WL position signal switch f. guide frame, 2nd block 6 micro-switches                                                                                                                                          |
| 173  | 3WL9111-0AP04-0AA0 | accessories circuit breaker 3WL shutter for guide frame 3p sz i, with locking device                                                                                                                                                       |
| 174  | 3WL9111-0AP06-0AA0 | accessories circuit breaker 3WL shutter for guide frame 3p size ii, with locking device                                                                                                                                                    |
| 175  | 3WL9111-0AP07-0AA0 | accessories circuit breaker 3WL shutter for guide frame 3p size iii, with locking device                                                                                                                                                   |
| 176  | 3WL9111-0AL07-0AA0 | accessories circuit breaker 3WL shutter for guide frame 3p size iii, with locking device                                                                                                                                                   |
| 177  | 3WL9111-0AL08-0AA0 | accessories circuit breaker 3WL maine conductor conn. 1 piece fixed-mounted circ.br. size I front conn. top dual hole front accessible up to 2000A                                                                                         |
| 178  |                    |                                                                                                                                                                                                                                            |
| 179  |                    |                                                                                                                                                                                                                                            |
| 180  |                    |                                                                                                                                                                                                                                            |
| 181  |                    |                                                                                                                                                                                                                                            |
| 182  |                    |                                                                                                                                                                                                                                            |